

Sika® FastFix-136 Road

Black, one component, multi-purpose, fast hardening micro-concrete for bedding, fixing and repair

USES



- Fixing of street furniture
- Repair of manhole and utility box covers
- Placing and repair of vehicle access ramps
- General repairs of traffic areas
- Fast laying of pavement blocks

ADVANTAGES

USE FOR ANY
VEHICULAR TRAFFIC

DIFFERENT
CONSISTENCIES

FAST STRENGTH DEVELOPMENT
(>20 MPA AFTER 2 H)

FAST RETURN TO
SERVICE

AESTHETIC,
BLACK

TEMPERATURES UP TO 35°C

FREEZE THAW
RESISTANCE

HIGH MECHANICAL
STRENGTH

KNOW-HOW FROM SITE TO SHELF



FOR MORE
SikaProduct®
INFORMATION

All orders are accepted subject to our current terms of sale and delivery.
Users should always refer to the most recent issue of the Product Data Sheet
for the product concerned.

Sika Services AG
Refurbishment
CH-8048 Zurich
Switzerland
Phone +41 58 436 23 68
www.sika.com

BUILDING TRUST



Sika® FastFix-136 Road MICRO-CONCRETE FOR FIXING AND REPAIR OF URBAN AREAS

Black colored, fast hardening,
adaptable consistency



BUILDING TRUST



Sika® FastFix-136 Road

BLACK FAST-HARDENING MICRO-CONCRETE FOR FIXING AND REPAIR IN URBAN AREAS AND VEHICLE TRANSIT ZONES

EASY APPLICATION

- One component, easy to mix
- Adapt only the water ratio to get the desired consistency during application
- Simple application - pouring and placing
- Fast setting

TIME SAVING

- Fast setting time and high early strength (> 20 MPa after 2 hours) once applied
- High layer thickness is possible - less application steps required
- Just pour and place, then it is done

AESTHETIC

- Dark color which harmonizes with the color of the surrounding asphalt
- Smooth finish



HOW TO MIX:

- Place minimum recommended water ratio in mixing container. Don't mix more than 2 bags at once.
- Progressively add powder whilst mechanically mixing, using low speed (max. 500 rpm) electric drill.
- Add more water to suit the desired consistency and flow properties, but not exceeding maximum dosage
- Mix for 3 minutes or until the material is homogenous



HOW TO APPLY:

- Prepare the substrate until it is clean, free from dust, loose material or other contamination.
- Pre-wet the surface.
- Mix the micro concrete with the desired consistency. Don't mix more than 2 bags at once. Mix until material is homogenous.
- Apply the micro concrete manually by placing (as a laying bed) or pouring (for fixing).
- Use a layer thicknesses up to 200 mm per application step. To add a higher layer thickness, wait until placed product started to harden.

