GLOBAL BUT LOCAL PARTNERSHIP





SikaSeal®-171 Glass Seal

Silicone for glazing applications



FOR MORE SEALING & BONDING INFORMATION:



Please consult the most current local Product Data Sheet prior to any use

Sika Services AG

Sealing & Bonding Tueffenwies 16 CH-8048 Zurich Switzerland Phone +41 58 436 40 40 www.sika.com



SikaSeal®-171 Glass Seal

VERSATILE AND UV RESISTANT ACETOXY SILICONE



BENEFITS / CHARACTERISTICS

- Low VOC emissions
- Very good resistance to UV exposure and weathering
- Movement capability ±20%
- Resistant to temperatures between -40°C to +100°C
- Airtight and waterproof elastic seal
- Solvent-free

APPROVALS / CERTIFICATES

- GEV Emicode EC1
- CE marking: EN 15651-1, EN 15651-2

COLORS

White, transparent











USES

- Suitable for interior and exterior glazing applications of residential homes
- It contains fungicide to protect the sealant for mold growth in humid areas
- Very good adhesion without a primer on many construction materials and substrates such as aluminum, glass, ceramic

EXAMPLES OF USE

■ Sealing glass to frame on greenhouses, winter garden and skylights, sealing glass on humid areas in residential homes, or interior decoration with glass walls



