GLOBAL BUT LOCAL PARTNERSHIP





SikaSeal®-177 Wall Repair

Acrylic sealant for interior



FOR MORE SEALING & BONDING INFORMATION:



Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

Sika Services AG

Sealing & Bonding
Tueffenwies 16
CH-8048 Zurich
Switzerland
Phone +41 58 436 40 40
www.sika.com





SikaSeal®-177 Wall Repair OVER-PAINTABLE ACRYLIC SEALANT FOR INTERIOR USE



BENEFITS / CHARACTERISTICS

- Easy to apply, tool and clean with water
- Very low emissions, free of solvents and phthalates
- Movement capability ±7.5%
- Can be stored at temperatures down to -10°C for a limited time (up to 24h), i.e.: for transport or storage

APPROVALS / CERTIFICATES

- GEV Emicode EC1 PLUS
- CE marking: EN 15651-1

COLORS

White











USES

- Suitable for sealing interior joints or repair wall cracks
- It can be painted over with most water-based paints
- Prevents further cracking or adhesion loss if low movement occurs
- Very good adhesion without a primer on construction materials and substrates such as concrete, brick, plastered surfaces, plasterboard, aluminum or wood

EXAMPLES OF USE

■ Sealing windowsills, door frames, lightweight walls, ceiling joints with low movement, filling holes and repair of cracks on walls



