

GLOBAL BUT LOCAL PARTNERSHIP



© SIKASERVICES AG / SEALING & BONDING / SIKASEAL-176 MASONRY / DR_C_SKSERV_010145 / 09.2023

BUILDING TRUST



SikaSeal®-176 Masonry

Acrylic sealant for exterior and interior use



FOR MORE SEALING & BONDING INFORMATION:



Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

Sika Services AG

Sealing & Bonding
Tueffenwies 16
CH-8048 Zurich
Switzerland
Phone +41 58 436 40 40
www.sika.com

BUILDING TRUST



SikaSeal®-176 Masonry

OVER-PAINTABLE ACRYLIC SEALANT FOR CONNECTION JOINTS



BENEFITS / CHARACTERISTICS

- Easy to apply, tool and clean with water
- Very low emissions, free of solvents and phthalates
- Very good resistance to UV exposure
- Movement capability $\pm 12.5\%$
- Can be stored at temperatures down to -10°C for a limited time (up to 24h), e.g.: for transport or storage

APPROVALS / CERTIFICATES

- GEV Ecodec EC1^{PLUS}
- CE marking: EN 15651-1

COLORS

White



USES

- Suitable for sealing low movement and connection joints in exterior and interior applications
- It can be painted over with most water-based paints
- Very good adhesion without a primer on construction materials and substrates such as concrete, brick, plastered surfaces, plasterboard, aluminum or wood

EXAMPLES OF USE

- Sealing interior and exterior connection joints, sealing interior window frames, door frames and windowsills, sealing joints between wall and ceiling, sealing joints in lightweight walls; filling holes and cracks on walls

